



2537 Wharton Glen Avenue, Mississauga, Ontario, L4X 2A8
Phone: (905) 277-9925 | Fax: (905) 277-9934 | www.combifab.com

TECHNICAL DATA SHEET

ET 611 (SC-211 US) HIGH PERFORMANCE SPLICING TAPE

Product Description

Ultra-Splice is a 3.6 mils, high performance polyester splicing tape. This product is a supported, high tack, fast grabbing, acrylic. Double coated pressure sensitive tape.

Application

- High Speed splicing of papers, films, foils and corrugated board
- Decorative parts
- General bonding

Features

- Tears easily by hand
- Fast grabbing adhesive
- Excellent holding power and heat resistance
- Polyester carrier is flexible/conformable adds dimensional stability
- Laminates well to a variety of substrates
- Performs well over a wide temperature range

Structure

	Release liner
	Acrylic adhesive
	Polyester carrier
	Acrylic Adhesive



2537 Wharton Glen Avenue, Mississauga, Ontario, L4X 2A8
Phone: (905) 277-9925 | Fax: (905) 277-9934 | www.combifab.com

TECHNICAL DATA SHEET

ET 611 (SC-211 US) HIGH PERFORMANCE SPLICING TAPE

Technical Data

Thickness without liner	3.6 mils
Carrier	polyester
Liner	white
Adhesive	Acrylic
Adhesion	48-52 oz/in
Temperature Application Range	15-25°C (59-77°F)
Operating Temperature	0°C to 130°C (32°F to 266°F)
Color	Transparent
Holding Power (1" x 1" x 1000g) @ RT	>24hr

LIMITED WARRANTY STATEMENT

Products are warranted to be free of defects in workmanship and material at time of shipment. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.