



2537 Wharton Glen Avenue, Mississauga, Ontario, L4X 2A8  
Phone: (905) 277-9925 | Fax: (905) 277-9934 | [www.combifab.com](http://www.combifab.com)

## TECHNICAL DATA SHEET

### **VT 525 FSK ALUMINUM FOIL TAPE**

#### *Product Description*

A tridirectional resinforce U.L. listed foil / scrim / kraft lamination. The tape conforms well to both fibrous duct board and blankets. Coated with a special cold weather acrylic pressure sensitive adhesive system, that combines superior quick stick at normal temperatures with superior low temperature performance at freezing (10°F). This is the ultimate in cold weather tapes. Recommended for use at normal and elevated temperatures also.

#### *Applications*

Primarily used as a vapor seal on FSK faced fiberglass ductboard and blanket systems.

#### *Technical Data*

<i>Test</i>	<i>Imperial</i>	<i>Metric</i>
Thickness	6.5 mils	0.165mm
Adhesion: Peel:	92 oz./in.	26 N/2.5cm
Loop Tack:	50 oz./in.	14 N/2.5cm
Shear: Indefinite@	2 PSI	13.8 kPa
Tensile	45 lbs./in.	203 N/2.5 cm
Elongation	2.00%	203 N/2.5 cm

Put up (widths): 1", 1-1/2", 1-3/4", 2", 2-1/2", 3", 4"

Standard Lengths: 50 yards (150 ft.)